

Fendt Momentum Specifications

	FTP16-30	FTP24-20	FTP24-22	FTP32-15	FTP24-30	FTP36-20	FTP36-22	FTP48-15
Rows / spacing in. (m)	16R 30 (76.2)	24R 20 (50.8)	24R 22 (55.88)	32R 15 (38.1)	24R 30 (76.2)	36R 20 (50.8)	36R 22 (55.88)	48R 15 (38.1)
Hitch on planter	2-pt or drawbar							
Metering units	vSet2 / vDrive*							
SeedTube options	Wave Vision SpeedTube							
CFS capacity bu. (L)	130 (4,581)							
Liquid fertilizer gal. (L)	1,000 (3,785.4)							
Est. weight (empty) lbs. (kg.)	23,000 (10,433)	26,000 (11,793)	26,000 (11,793)	29,000 (13,154)	29,000 (13,154)	34,000 (15,422)	34,000 (15,422)	38,000 (17,237)
Transport width ft. (m)	12 (3.65)							
Transport height ft. (m)	12 (3.65)							
Est. tongue weight lbs. (kg.)	8,000 (3,629)	9,000 (4,082)	9,000 (4,082)	10,000 (4,536)	10,000 (4,536)	11,500 (5,216)	11,500 (5,216)	13,000 (5,897)
Tractor HP	8-12 HP per row 10-20 HP per row							
Hydraulic requirements GPM (LPM)	35-60 (132-227)							